

CERTIFICATE OF ANALYSIS

BRETON® SEL GRIS® - FRENCH GREY SEA SALT - BRUT

PASSED

CERTIFICATE OF ANALYSIS | OFFICIAL SALTWORKS DOCUMENT | DATE OF APPROVAL: 01/02/2025

DESCRIPTION



DESCRIPTION: Sel Gris - French grey sea salt is sea water evaporated from clay lined ponds, hand-harvested using traditional methods.

GRANULOMETRY: Brut Grain 2.0 mm – 5.0 mm

INGREDIENTS: Sea Salt

ADDITIVES: Does not contain anti-caking agents, free-flowing agents, or conditioners.

APPEARANCE: Light grey natural crystals

COUNTRY OF ORIGIN: France

PROCESSED & PACKAGED: Woodinville, WA

SHELF LIFE: Minimum 10 years from production date.



OPTICALLY CLEAN®




CERTIFIED AUTHENTIC



ORGANIC COMPLIANT



KOSHER




SEA SALT



SQF CERTIFIED

CHEMICAL ANALYSIS*




| PARAMETER | RESULTS* | SPECIFICATION |
|------------------------|-------------|---------------|
| Chloride (CL) | 601,800 ppm | NS* |
| Sodium (NA) | 388,000 ppm | NS* |
| Sodium Chloride (NaCl) | 99.30% | > 93.0% |
| Calcium (Ca) | 922 ppm | NS* |
| Iodine (I) | < 1.0 ppm | NS* |
| Magnesium (Mg) | 3,230 ppm | NS* |
| Potassium (K) | N/A | NS* |
| Insolubles | 0.51% | NS* |
| Moisture | 1.77% | NS* |
| Arsenic (As) | 0.078 ppm | < 0.50 ppm |
| Cadmium (Cd) | < 0.01 ppm | < 0.50 ppm |
| Copper (Cu) | 0.153 ppm | < 2.00 ppm |
| Chromium (Cr) | 0.35 ppm | < 0.50 ppm |
| Lead (Pb) | 0.584 ppm | < 1.00 ppm |
| Mercury (Hg) | < 0.005 ppm | < 0.10ppm |

*Chemical analysis for this salt is conducted annually. If a lot-specific analysis is needed, additional time and costs will be incurred.


Specification values are based on Codex Standard 150:1985. Due to rounding, the total may not equal 100%. "NS" indicates no specification under Codex Standard 150:1985.

GRANULOMETRY



| GRAIN | LOW AVERAGE | HIGH AVERAGE |
|-------|-------------|--------------|
| BRUT | 2.0 mm | 5.0 mm |

PACKAGING DATA



Packaging Size: 5 lb | 55 lb | 2,200 lb

Packaging Type: Poly Bag

Pallet Size: 48 x 40 x 48

Pallet Type: Hardwood Pallets-Domestic/Plastic pallets-International

STORAGE CONDITIONS



To improve caking resistance, store in a dry, airtight environment with a humidity level below 75%. The temperature should be ambient.

BASE SALT ORIGIN



FRANCE



Britta Pyle

QA Manager, Saltworks®, Inc.

01/02/2025

Date

NOTICE: All of the above statements, recommendations, suggestions and data are based on our laboratory results, and we believe the same to be reliable. Nevertheless, with the exception of data showing an express guaranty (such as in the case of products specifically designed for use as nutrient supplements), all such statements, recommendations, suggestions and data herein above presented are made without gauranty, warranty or responsibility or any kind on our part. All data above is property of SaltWorks® Inc. and may not be reproduced without expressed written consent.

| | | | | |
|--------------|-----------|----------|----------|------|
| Invoice Date | Invoice # | Lot Code | Customer | PO # |
|--------------|-----------|----------|----------|------|